

JJRZ 56-5.18



Boom Specifications

Vertical Reach	55.2 m (181'1")
Horizontal Reach	51.2 m (168')
Unfolding Height	11.3 m (37'1")
1st Section Length	11.3 m (37'1")
2nd Section Length	9.9 m (32'5")
3rd Section Length	9.8 m (32'2")
4th Section Length	10.4 m (34'1")
5th Section Length	9.8 m (32'2")
Swing and Vertical Extension	
Front Spread	11.4 m (37'4")
Rear Spread	11.3 m (37'1")

General Specifications

Pipe Size (ID)	125 mm (5")
Elbow	All Standard Size
Coupling Size	140 mm (5.5")
End Hose Length	4 m (13')
Boom Control Valve	Proportional (by HAWE)
Proportional Ratio	Standard
Remote Control	
Wire Remote Control	Standard
Vibrator	Standard
Water Pump	Rust proof hydraulic power 20bar (290psi)
Water Tank	800 L (211 G)

Pump Specifications

Output	Rod Side	181 m ³ /h (237 yd ³ /h)
	Piston Side	122 m ³ /h (160 yd ³ /h)
Pressure	Rod Side	85 Bar (1233 psi)
	Piston Side	130 * bar (1886 psi)
Concrete Cylinder Diameter	230 mm (9")	
Concrete Cylinder Type	Hard Chromed	
Stroke Length	2100 mm (83")	
S-Tube Size	8" X 7"	
Main Oil Pump	Tandem Rexroth Hydromatic A20V0190	
Hydraulic System Pressure	350 bar (5075 psi)	
Lube System (Hopper)	Automatic	
Switching System	Hydraulic	
Hopper Capacity	Easy Clean 600 L (158 G)	
Number of Strokes/Min	34	
Output Control Range	20(26)~164m ³ /h(215yd ³ /h)	

* Not to be used through Boom Pipe

Other Chassis and Pump Cells available contact your sales representative.

Alliance Concrete Pumps Inc. reserves the right to make changes to these specifications.

JJRZ 56-5.18

