



# 38 METER Z-FOLD

**75% ROAD BAN LEGAL**

**4 SECTION**

**BOOM PUMP**



JXLZ 38-4.10\*

## BOOM SPECIFICATIONS

Vertical Reach	37.1 m (121'9")
Horizontal Reach	33.1 m (108'7")
Reach from Front - Cabover	30.3 m (99'5")
Unfolding Height	8.9 m (29'2")
1st Section Length	8.98 m (29'5")
2nd Section Length	7.85 m (25'9")
3rd Section Length	7.94 m (26'1")
4th Section Length	8.33 m (27'4")
Outrigger	X - Style
Front Spread	6.3 m (20'8")
Rear Spread	7.0 m (23')

## GENERAL SPECIFICATIONS

Pipe Size (ID)	125 mm (5")
Boom Control Valve	Proportional (by HAWE)
Radio Remote:	Dual Wireless Transmitter System
Vibrator	Standard
Water Pump	Hydraulic Power 20 bar (290 psi)
Water Tank	800 L (211 G)
Wear Parts	Carbide
Popular Upgrades*	LED Boom Light Kit LED Outrigger Lights Heated Water Tank Heated Hydraulic Tank Air-Cuff Twin Wall Pipe

\*more options available, ask your sales rep for details.

## PUMP SPECIFICATIONS

Output	Rod Side	96 m <sup>3</sup> /h (126yd <sup>3</sup> /h)
	Piston Side	63 m <sup>3</sup> /h (82 yd <sup>3</sup> /h)
Pressure	Rod Side	76 bar (1102 psi)
	Piston Side	112 <sup>†</sup> bar (1625 psi)
Concrete Cylinder Diameter	200 mm (8")	
Concrete Cylinder Type	Hard Chromed	
Stroke Length	1600 mm (63")	
S-Tube Size	8" X 7"	
Main Oil Pump	Kawasaki 180cc	
Hydraulic System Pressure	350 bar (5076 psi)	
Lube System (Hopper)	Automatic	
Switching System	Hydraulic	
Hopper Capacity	Easy Clean 600 L (158 G)	
Number of Strokes/Min	31	
Output Control Range	5(7)~96m <sup>3</sup> /h (126yd <sup>3</sup> /h)	

<sup>†</sup>Not to be used through boom pipe.

\*Contact your sales representative for alternate chassis options.

[www.allianceconcretepumps.com](http://www.allianceconcretepumps.com)



# JXLZ 38-4.10

**BOOM PUMP**

1.888.584.7231 1.888.870.0908

## CONVENTIONAL CAB

Reach from front: 29.6m (97'2")



## DIAGRAMS

